


Globe valve V46 class2500, F91

Globe valve regulating V40 class2500, F91



22		
21		
20		
19		
18		
17		
16		
15	H.W.Lock Nut	Carbon Steel
14	Handwheel	A197
13	Stem Nut	ASTM A276 410
12	Nut	A194 8
11	Gland flange	ASTM A105
10	Gland	ASTM A276 410
9	Bolt	A193 B8
8	P.S Nut	ASTM A276 410
7	Stem packing	SS304+Graphite
6	Bonnet	ASTM A182 F91
5	Sealing ring	ASTM A276 410
4	Sealing holder	ASTM A276 420
3	Stem	ASTM A182 F6a
2	Disc	AISI 420+STL
1	Body (+Seat)	A182 F91+STL
No	Partname	Material

TECHNICAL REQUIREMENTS

- 1: Design and manufacture as per API 602
- 2: Socket weld as per ANSI B16.11
- 3: Valve inspection and test as per API 598
- 4: Face to face as per manufacturer's standard.
- 5: Reduced bore

CLASS	2500	LB
SHELL TEST PRE(HYD)	64.0	MPa
SEAT TEST PRE(HYD)	46.9	
SEAT TEST PRE(AIR)	0.6	

CLASS: 2500#

NPS	L	H _{open}	ϕW	ϕS	T	D
1/2"	186	330	200	21.8	10	10.5
1"	186	330	200	33.9	13	17.5
1-1/2"	220	476	250	48.8	13	29
2"	279	522	300	61.2	16	35

Drawing		Time		Tel		
Check		NO.		Fax		