


Globe valve V46 class800, A105

Globe valve regulating V40 class800, A105



22		
21		
20		
19		
18		
17		
16		
15		
14	H.W.Lock Nut	Carbon Steel
13	Handwheel	A197
12	Stem Nut	ASTM A182 F6a
11	Nut	A194 2H
10	Gland Flange	ASTM A105
9	Gland	ASTM A182 F6a
8	Bolt	A193 B7
7	Stem Packing	Graphite
6	Bonnet Bolt	A193 B7
5	Bonnet	ASTM A105
4	Gasket	SS304+Graphite
3	Stem	ASTM A182 F6a
2	Disc	ASTM A182 F6a
1	Body	ASTM A105
No	Partname	Material

TECHNICAL REQUIREMENTS

- 1: Design and manufacture as per API 602
- 2: Socket weld as per ANSI B16.11
- 3: Valve inspection and test as per API 598
- 4: Face to face as per manufacturer's standard.
- 5: Reduced bore

CLASS 800 L B

SHELL TEST PRE(HYD)	20.5	
SEAT TEST PRE(HYD)	15.0	MPa
SEAT TEST PRE(AIR)	0.6	

CLASS: 800#

NPS	L	H _(open)	ϕW	ϕS	T	D
1/2"	79	165	100	21.8	10	10.5
1"	111	202	125	33.9	13	17.5
1-1/2"	152	258	160	48.8	13	29
2"	172	298	180	61.2	16	35

Drawing	Time	Tel		
Check	NO.	Fax		